

Din Mounted Change Over Switch CO-MOD-40



DESCRIPTION / APPLICATION

The product is used as switch on and off, conversion and isolation, can be used in a group of line with two loads, as well as dual power supplies. It is in conformity of IEC60947-3 standard.

MAIN TECHNICAL DATA

Rated operational voltage	240/415VAC
Poles	1P,2P,3P,4P

Rated current	16,25,32,40,63A
Rated frequency	50/60Hz
Contact form	1-0-2
Degree of protection	IP20
Torgue setting	1.8-2 N/m
Mounting	On 35mm DIN rail by fast clip device. Note: busbar is required for 63A switch, 16m m ² wire is not fit
Ambient Temperature	-5... +40°C

INSTRUCTION FOR USE

2P MTS:

1. When the handle hits the I position: 1 and 2, 5 and 6 are connected
2. When the handle hits the II position: 1 and 4, 5 and 8 are connected
3. When the handle is in the middle position: both groups are disconnected.

4P MTS:

1. When the handle hits the I position: 1 and 2, 5 and 6, 2 and 9, 6 and 13 are connected

2. When the handle hits the II position: 1 and 4, 5 and 8, 4 and 9, 8 and 13 are connected

3. When the handle is in the middle position: both groups are disconnected.

DIMENSIONS

