



Lithium Button Cells, 3V



Main Features

- Electrochemical System: Lithium manganese dioxide
- Nominal Voltage: 3,0V
- Jacket: stainless steel
- High energy density
- Shelf life approx. 10 years
- Ideal for computers, calculators, cameras, heart rate monitor, alarm systems
- Available as 1 pcs and 5 pcs blister

Technical Data

| Frame size | CR1216 | CR1220 | CR1225 | CR1616 | CR1620 | CR1632 | CR2016 | CR2025 | CR2032 | CR2320 | CR2325 | CR2330 | CR2430 | CR2450 | CR2477 | CR927 |
|--------------------------|-----------------------------|-----------------------------|-----------------------------|-----------------------------|-----------------------------|------------------------------|-----------------------------|------------------------------|------------------------------|------------------------------|------------------------------|------------------------------|------------------------------|------------------------------|--------------------------------|-----------------------------|
| Dimensions (Ø x H mm) | 12,5 x 1,6 | 12,5 x 2,0 | 12,5 x 2,5 | 16,0 x 1,6 | 16,0 x 2,0 | 16,0 x 3,2 | 20,0 x 1,6 | 20,0 x 2,5 | 20,0 x 3,2 | 23,0 x 2,0 | 23,0 x 2,5 | 23,0 x 3,0 | 24,5 x 3,0 | 24,5 x 5,0 | 24,5 x 7,7 | 9,5 x 2,7 |
| Weight (g) | 0,7 | 0,9 | 1,0 | 1,2 | 1,3 | 2,0 | 1,8 | 2,5 | 3,1 | 3,0 | 3,3 | 4,0 | 4,2 | 6,2 | 10,5 | 0,6 |
| Nominal Capacity | 25mAh to 2V (20° ± 2° C) | 38mAh to 2V (20° ± 2° C) | 50mAh to 2V (20° ± 2° C) | 50mAh to 2V (20° ± 2° C) | 70mAh to 2V (20° ± 2° C) | 120mAh to 2V (20° ± 2° C) | 75mAh to 2V (20° ± 2° C) | 150mAh to 2V (20° ± 2° C) | 220mAh to 2V (20° ± 2° C) | 130mAh to 2V (20° ± 2° C) | 190mAh to 2V (20° ± 2° C) | 260mAh to 2V (20° ± 2° C) | 270mAh to 2V (20° ± 2° C) | 550mAh to 2V (20° ± 2° C) | 1.000mAh to 2V (20° ± 2° C) | 30mAh to 2V (20° ± 2° C) |
| | rated capacity at 62kΩ | rated capacity at 62kΩ | rated capacity at 62kΩ | rated capacity at 30kΩ | rated capacity at 1mA | rated capacity at 15kΩ | rated capacity at 30kΩ | rated capacity at 15kΩ | rated capacity at 15kΩ | rated capacity at 15kΩ | rated capacity at 15kΩ | rated capacity at 15kΩ | rated capacity at 15kΩ | rated capacity at 15kΩ | rated capacity at 7,5kΩ | rated capacity at 4,7 |
| continuous drain | | | | | | | | | | | | | | | | |

Technical and logistical changes reserved