



PART NUMBERS

S	RF50H	XX	YY
COMPANY CODE	PRODUCT SERIES	NOMINAL CURRENT	VOLTAGE

DC FUSE BASE / HOLDER

Product model	CH-50H / SRD-50H
Citation standards	IEC/EN60947-1 IEC/EN 60947-3
Rated insulation voltage Ui	1600V
Rated service voltage Ue	DC1500V
Rated service current Ie	2/3/4/5/6/8/10/12/15/16/20/25/30/32/35/40/45/50A
Rated impulse withstand voltage	8kA
Rated acceptable power dissipation	≤12W
Numbers of poles	1P
Rated limiting short circuit current	50kA
Fuse dimensions for use	10mm×85mm 14mm×85mm
Ingress protection	IP20
Us category	PV-0

CONTINUES...

DC FUSE	
Product Model	SRF-25H
Rated voltage	1500VDC
Rated insulation voltage Ui	2/3/4/5/6/8/10/12/15/16/20/25A
Rated accepted power dissipation	2.5W
Size	10mm×85mm
Rated short circuit breaking capacity	20kA
Reference Standard	EN 60269-1 / EN 60269-6
Protection level	IP20
Use category	PV-0
Fuse dimensions for use	10mm×38mm
Ingress protection	IP20

DC FUSE	
Product Model	SRF-50H
Rated voltage	1500VDC
Rated insulation voltage Ui	8/10/12/15/16/20/25/30/40/50A
Rated accepted power dissipation	2.5W
Size	14mm×85mm
Rated short circuit breaking capacity	20kA
Reference Standard	EN 60269-1 / EN 60269-6
Protection level	IP20
Use category	PV-0
Fuse dimensions for use	10mm×38mm
Ingress protection	IP20

