




- COMPONENTS FULLY COMPLIANT NCRS (LOA & RCC)
- PRE-POPULATED
- ECONOMIC
- NEUTRAL BAR & EARTH BAR FITTED
- AESTHETICALLY PLEASING

PART NUMBER

D B 2 - 0 8 S F + K I T - A



SPECIFICATIONS	
MATERIAL (MAIN BOX / LID)	ABS BODY/STEEL TRAY/PC (POLYCARBONATE)WINDOW
MOUNTING TYPE	STEEL FLUSH MOUNT / DIN RAIL FOR COMPONENTS
MAX VOLTAGE, CURRENT AND FAULT RATING	240V 63AMP 3KA
IP (Ingress Protection Rating) RATING	IP40
CONTAINS (KIT-A)	<ul style="list-style-type: none"> • INCOMER ISOLATOR : ISO – 63 2P • EARTH LEAKAGE : EL – 63 1P + N • CIRCUIT BREAKER : 20A 1P 3KA (x 2) • CIRCUIT BREAKER : 10A 1P 3KA (x 1) • BUSBAR - BB 3 MOD (x 1)
WEIGHT (POPULATED)	1.86 Kg

CONTINUES...

DIMENSIONS**SAFETY NOTES**

- TO BE INSTALLED, TESTED AND COMMISSIONED BY A QUALIFIED ELECTRICIAN
- DANGER - LETHAL VOLTAGES INSIDE

APPLICATIONS

- FOR INDOOR OR UNDERCOVER DOMESTIC INSTALLATIONS
- IDEAL FOR SMALL HOMES, OUTBUILDINGS, SMALL WORKSHOPS, CONTAINERS, ETC.

RELATED PRODUCTS

- | | |
|------------------|-----------------------------------|
| • ISOLATORS | • CIRCUIT BREAKERS |
| • EARTH LEAKAGES | • BUSBARS, SAFETY LABELS, LEGENDS |

DOCUMENT TRACKING & CATALOGUE LINK

EDITED BY	DATE	APPROVED BY	DATE
BIANCA F.	25 JAN 2024	STEVAN ELION	25 JAN 2024