



| 公差等级/General Tolerances(mm) | | 公差等级/General Tolerances(mm) | | | | | | | | | | 公差等级/General Tolerances(mm) | | |
|-----------------------------|-------|-----------------------------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-----------------------------|-------|----------|
| 0 | >3 | >6 | >10 | >18 | >30 | >50 | >80 | >120 | >180 | >250 | >315 | >400 | >500 | 0.1/1/10 |
| ~ | ~ | ~ | ~ | ~ | ~ | ~ | ~ | ~ | ~ | ~ | ~ | ~ | ~ | ±Z |
| ±0.12 | ±0.18 | ±0.22 | ±0.26 | ±0.31 | ±0.37 | ±0.57 | ±0.80 | ±1.05 | ±1.15 | ±1.60 | ±2.20 | ±2.50 | ±2.50 | ±Z |

| ITEM | NAME OF PART | MATERIAL | NOTES |
|------|-----------------|----------|--------------|
| 4 | Cage | Steel | M3/Zn Plated |
| 3 | Current carrier | Copper | Sn Plated |
| 2 | Screw | Steel | M3/Zn Plated |
| 1 | Housing | PA66 | UL94V-0 |

| REV | ECN | DESCRIPTION | DRAFT | DATE |
|-----|-----|-------------|-------|------|
| 1 | | | | |
| 2 | | | | |
| 3 | | | | |
| 4 | | | | |

| | |
|--------------------------|--|
| MATERIAL: / | SURFACE: / |
| MAT NO.: / | |
| STATUS: / | |
| APPD: Li GL 2020.05.15 | NAME: DEGSON® NINGBO DEGSON ELECTRICAL CO., LTD |
| CHKD: Moo J 2020.05.15 | DC4-01P-1Y-00A(H) |
| DRAFT:Wong LX 2020.05.15 | DRAWING NO.: DC4-C01 |
| | TYPE: CUSTOMER DRAWING |
| | SCALE: 2:1 |
| | REV: D0-1 |
| | SHEET: 1/1 |

| UL 标准/UL Standard: | B | C | D |
|---|--------------|--------|-------|
| 额定电压/电涌/Rated Voltage(V)/Current(A) | 600/30 | 600/30 | 600/5 |
| IEC 标准/IEC Standard: | | | |
| 额定电压/电涌/Rated Voltage(V)/Current(A) | 1000/32 | / | / |
| 额定脉冲电压(KV)/Rate Impulse Voltage(KV) | 8.0 | / | / |
| 额定扭矩/Torque Tightening(N·m/Lb.in) | M3, 0.66/6.0 | | |
| 线径范围(裸线/绞线)/Wire Range(rigid and flexible)(mm²/AWG) | 0.5~4/22~10 | | |
| 厚度/Pitch(mm) | 6.1 | | |
| 剥线长度/Stripping length(mm) | 8~9 | | |
| 使用温度范围/Operating Temperature(°C) | -40~+105 | | |
| 符合RoHS要求/Conform to RoHS | Yes | | |
| 标准颜色编号/Standard color number: | / | | |
| PANTONE / RAL | / | | |