

PROFESSIONAL GRADE PVC INSULATION TAPE

0.18mm x 18mm x 20m

GENERAL DESCRIPTION:

A professional grade PVC Electrical Insulation Tape that provides excellent electrical insulation with high adhesion, which can be applied over a wide temperature range. Once applied it provides high grade electrical insulation up to 600V within varying weather conditions.

- Flame retardant
- Insulation up to 600 Volt
- UL listed 57RJ
- PolyVinyl Chloride (PVC) backing
- Flexible and conformable to awkward shapes
- Water resistant
- UV resistant
- Non-corrosive adhesive

TECHNICAL DATA

| | |
|----------------------|--|
| Colours: | Black, Red, Blue, Yellow, Green, White |
| Thickness: | 0.18mm as per ASTM D1000 |
| Length: | 20 meter |
| Width: | 18 mm |
| Flame Retardant: | UL57RJ pass |
| Breaking Load: | 30 n/cm |
| Elongation: | 240% as per AMSTD1000 |
| Adhesion to steel: | 2.2 n/cm |
| Adhesion to it self: | 2.0n/cm |
| Break down Voltage | 6.0 kV |
| Service Temperature | -10°C to +80C |



LISTED 57RJ
CAT NO. 1920

NOTE

Except where indicated otherwise, the figures stated are test average values and should not be regarded as MAXIMUM or MINIMUM values for specification purposes. The Company reserves the right to improve products and any change in specification will result in a re-issue of the relevant 'Technical Data Sheet'.

| PRODUCT NUMBER | COLOUR | BARCODE | CASE SIZE | CARTON WEIGHT | QTY |
|----------------|--------|---------------|---------------------|---------------|-----|
| 61010 | Black | 0707273544889 | 20m X 18mm X 0.18mm | 22.3 kg | 250 |
| 61020 | Red | 0707273544902 | 20m X 18mm X 0.18mm | 22.3 kg | 250 |
| 61030 | Blue | 0707273544896 | 20m X 18mm X 0.18mm | 22.3 kg | 250 |
| 61040 | Yellow | 0707273544926 | 20m X 18mm X 0.18mm | 22.3 kg | 250 |
| 61050 | Green | 0606110159982 | 20m X 18mm X 0.18mm | 22.3 kg | 250 |
| 61060 | White | 0707273544919 | 20m X 18mm X 0.18mm | 22.3 kg | 250 |